

# Polycom® VVX® Expansion Module

Turn your Polycom VVX business media phone into a cost-effective attendant console.



## DATA SHEET

---

The Polycom® VVX Expansion Module is a cost-effective solution for telephone attendants, receptionists, administrative staff, and other dispatchers who manage multiple simultaneous telephone calls on a daily basis.

### Increase Productivity

The VVX Color Expansion Module provides advanced call handling capabilities using directory cards that simplifies monitoring/dispatching of a high number of static contacts.

### Ease of Use

Bi-color LEDs offer flexible and intuitive call visualization matching VVX phones.

### Extended Compatibility

Supports all VVX business media phones for maximum flexibility.

### Flexible paper directory

Quickly generate and print PDF template containing line key assignments.

### Leverage previous IT infrastructure investment

Get the most out of your Polycom VVX business media phones by turning them into cost-effective attendant solutions.

**DATA SHEET** Polycom VVX Expansion Module Specifications

---

## Features and Specifications

### Feature Keys

- 40 multifunctional line keys configurable as line registration, call appearance, speed dial, DSS, or BLF
- Dual-color (red or green) illuminated LEDs for line status information

### Compatible VVX phone models

- Polycom® VVX® 300/310
- Polycom® VVX® 400/410
- Polycom® VVX® 500
- Polycom® VVX® 600

### Communication with host phone and/or other modules

- 2 auxiliary ports (RJ-11)

### Expandability

- Up to three VVX Expansion Modules can be attached to any VVX phone

### Feature support

- Additional line registrations (up to 34 total)
- Shared call appearance, bridge line appearance (Key stem emulation)
- Call transfer
- Busy lamp field
- Speed dial
- Fully programmable line appearances

### Power

- Provided by Polycom VVX host phone
- Host phone powering options: IEEE 802.3(af/at) POE or using a compatible external AC adapter
- Powering starts automatically upon auxiliary port connection
- No additional power source is required

### Approvals

- CE Mark
- VCCI
- C-Tick

### Safety

- UL 60950-1
- CAN/CSA-C22.2 No. 60950-1
- EN 60950-1
- IEC 60950-1
- AS/NZS 60950-1

### Operating Conditions

- Temperature: 0-40° C (+32-104° F)
- Relative Humidity: 5%-95%, noncondensing

### Storage Temperature

- -40- 70° C (-40-160° F)

### VVX Expansion Module ships with

- VVX Expansion Module console
- VVX Expansion Module desk stand
- Attachment bracket with hand screws (2)
- Auxiliary cable
- Quick Start Guide

### Dimensions

- 5 in x 5 in x 6.5 in (12.5 cm x 12.5 cm x 16 cm) (W x H x D)

### Weight

- Physical: 1 lb (0.4kg)
- Unit Box: 1.32 lb (0.6 kg)

### Master carton quantity

- Ten (10)

### Warranty

- 1 year

### Country of Origin

- China

### Part number/UPC Code

- 2200-46300-025 / 610807781479

### Available accessories

- Wallmount



